OF SAUNA

Chimney set Barrel sauna

Kit de cheminée pour sauna baril



	Name/Quantity	ENG
A1	Single-wall chimney 0,25 m	
A2	Single wall chimney 0,5 m	
K	Single wall chimney adapter , cuttable 150 - 250 mm	
D	Double wall weldedchimney base	
F2	Cover plate for penetration of slopped ceiling, double-wall (two parts)	
O	T600 insulation plate for wall and ceiling	
L	Universal rubber roof flashing	
M	Rain collar	
H3	Double wall chimney 1,0 m	
J	Chimney cap	

Please ensure that there is a safety distance of at **least 500mm** between the steel chimney and any combustible materials for single wall components (A1, A2), and a **minimum of 50mm** for double wall components (H3).

	Nom/Quantité	FRA
A1	Conduit de cheminée simple paroi 0,25 m	
A2	Conduit de cheminée simple paroi 0,5 m	
K	Adaptateur de cheminée à paroi simple, découpable 150 - 250 mm	
D	La base du conduit de cheminée est soudée.	
F2	Plaque de couverture double paroi pour l'ouverture dans le plafond incliné	
O	Plaque isolante T600 pour mur et plafond	
L	Solin de toit en caoutchouc universel	
M	Corniche de protection contre la pluie	
H3	Conduit de cheminée double paroi 1,0 m	
J	Chapeau de cheminée	

Assurez-vous qu'il y ait une distance de sécurité **d'au moins 500 mm** entre la cheminée en acier et tout matériau inflammable pour les composants à paroi simple (K, A1, A2) et un **minimum de 50 mm** pour les composants à double paroi (H3).

A1

D

H3

M

A2

F2

J

K

O

L